



2015

DISTRIBUTOR EQUIPMENT

Hotley®

500 SERIES

and Model 680SS

- Oil-Fired or LP-Fired
- 115V/1PH
- 1725 RPM Direct-Drive Pump
- 7-Year Pump Warranty



Model 555SS (Shown with optional hose reel)



Model 558-Propane (Shown with optional Portagear & Propane Tank)



Model 560SS (Shown with optional hose reel)



Model 680SS

The **500 Series** delivers rugged, yet affordable, cleaning power for a broad range of applications, from agriculture to building maintenance. The sporty 555SS, with its stainless steel coil skin, is our most popular entry level hot water model—compact, evenly balanced, easy to maneuver, and engineered with the operator in mind. As with the entire Hotsy line, all models in the 500 series are ETL safety certified to UL-1776, with Hotsy pumps backed by a 7-year limited warranty. A pressure switch is standard on all 500 Series models. Equipped with a 50' hose.

MODEL	PART NO.	GPM	PSI	HP	VOLT/PH	AMPS	FUEL	BTU/HR	PUMP MODEL	PORTABILITY	DIMENSIONS	SHIP WT (lbs)
555SS	1.109-033.0	2.2	1300	2	115/1	20	Oil	214,300	Duplex - HHC165L.1	Std	33"Lx27"Wx41.5"H	360
558	1.109-610.0	2.2	1300	2	115/1	18	LP	227,000	Duplex - HHC165L.1	Optional	31.5"Lx26"Wx41"H	350
560SS	1.109-034.0	2.1	1500	2.3	115/1	20	Oil	214,300	Triplex - HHC205L.1	Std	33"Lx26"Wx44"H	395
680SS	1.109-035.0	3.0	1000	2	115/1	20	Oil	289,900	Triplex - HHC235R.1	Std	33"Lx27"Wx45.5"H	405

SS=Stainless Steel

BUNDLE PACKS Mix & Match any combination of the 555SS, 560SS & 680SS **3 PK = 2% OFF; 5 PK = 3% OFF; 10 PK = 5% OFF**

OPTIONS

PART NO.	DESCRIPTION
8.717-728.0	8" LP Gas-Fired Draft Diverter, Model 558
8.717-764.0	8" Oil-Fired Draft Dampener, Models 555SS/560SS/680SS
8.903-049.0	Portagear, Model 558

OPTIONS

PART NO.	DESCRIPTION
8.717-791.0	Propane Tank, 43 lb.
8.903-034.0	Float Tank, 555SS (Field Install)
8.750-486.0	360° Pivot Reel, 100' (fits all 500 Series EXCEPT 558)

700 SERIES

and Model 895SS

- Oil-Fired, LP- or Natural-Gas-Fired
- 7-Year Pump Warranty
- Direct- & Belt-Drive



Model 790SS



Model 771-Propane (Shown with optional Portagear & Propane Tank)



Model 895SS

The **700 Series** offers a nice balance of Hotsy ruggedness and cleaning performance, yet the affordability of an entry-level machine. In addition to the two direct-drive models, this series also offers belt-drive models that clean at 3.5 GPM and 2000 PSI. More powerful yet is the 895SS. The multiple fuel and electrical options makes the 700 series ideal for meeting the needs of commercial customers. All models are ETL safety certified and feature the Hotsy Triplex pump with a 7-year warranty. A pressure switch is standard on all 700 Series models. Equipped with a 50' hose.

MODEL	PART NO.	GPM	PSI	HP	VOLT/PH	AMPS	FUEL	BTU/HR	PUMP MODEL	DRIVE	PORTABILITY	DIMENSIONS	SHIP WT (lbs)
771	1.109-611.0	3.0	1500	3	230/1	13	LP	280,000	HHC235R.1	Direct	Optional	32"Lx27"Wx45.5"H	415
772	1.109-037.0	3.0	1500	3	230/1	13	NG	338,000	HHC235R.1	Direct	N/A	32"Lx27"Wx45.5"H	415
790SS	1.109-612.0	3.0	2000	4TEFC	230/1	20	Oil	289,900	HHC340R.1	Belt	Std	37"Lx28"Wx45.5"H	450
795SS	1.109-039.0	3.5	2000	5	230/1	24	Oil	289,900	HHC340R.1	Belt	Std	37"Lx28"Wx45.5"H	455
795SS-208	1.109-040.0	3.5	2000	5	208/1	27	Oil	289,900	HHC340R.1	Belt	Std	37"Lx28"Wx45.5"H	500
895SS	1.109-077.0	3.5	3000	8.2	230/1	36	Oil	289,900	HHC506R.1	Belt	Std	37"Lx28"Wx45.5"H	480

SS=Stainless Steel

OPTIONS

PART NO.	DESCRIPTION
8.717-728.0	8" Natural Gas- or LP Gas-Fired Draft Diverter, Models 771/772
8.717-764.0	8" Oil-Fired Draft Dampener, Models 790SS, 795SS & 895SS
8.903-049.0	Portagear, Model 771
8.717-791.0	Propane Tank, 43 lb.

OPTIONS

PART NO.	DESCRIPTION
8.750-486.0	360° Pivot Reel, 100'
8.750-483.0	360° Pivot Reel, 200' (Hose Reels fit all 700 Series Models EXCEPT 771/ 772)

Hot Water **ELECTRIC** Pressure Washers



800 SERIES

- Oil-Fired
- Big & Beefy, Yet Easy To Maneuver
- Rugged Hotsy Pump with 7-Year Warranty
- Stainless-Steel Coil Skin



Shown with optional hose reel

The new 800 Series - rugged design, easy maneuverability and massive cleaning power. Comparable to the cleaning power of Hotsy's heavy-duty stationary units, the big and beefy 800 Series is surprisingly easy to maneuver into place, allowing you to tackle the heaviest of industrial cleaning jobs. The 28" wide wheel base helps with stability, yet is narrow enough to fit easily through doorways. Components are protected by an easy-to-remove cover allowing servicing access. All 800 series hot water pressure washers are backed by a 7-year warranty on the Hotsy Triplex pump. A pressure relief valve, upstream detergent injector and stainless steel coil wrap are standard features on all 800 Series models, which are ETL certified. Equipped with a 50' hose.



MODEL	PART NO.	GPM	PSI	HP	MOTOR RPM	VOLT/PH	AMPS	FUEL	BTU/HR	PUMP MODEL	DRIVE	PORTABILITY	DIMENSIONS	SHIP WT (lbs)
821	1.109-120.0	4.0	2300	6.2	3450	208/1	33	Oil	342,900	HHC506R.2	Belt	Std	51"Lx28"Wx51"H	632
842	1.109-121.0	4.0	2000	5	1725	208/3	20	Oil	342,900	HH406R.2	Belt	Std	51"Lx28"Wx51"H	622
843	1.109-122.0	4.0	2000	5	1725	230/1	29	Oil	342,900	HH406R.2	Belt	Std	51"Lx28"Wx51"H	622
844	1.109-123.0	4.0	2000	5	1725	230/3	19	Oil	342,900	HH406R.2	Belt	Std	51"Lx28"Wx51"H	622
845	1.109-124.0	4.0	2000	5	1725	460/3	10	Oil	342,900	HH406R.2	Belt	Std	51"Lx28"Wx51"H	691
851	1.109-125.0	4.0	3000	8.2	3450	208/1	44	Oil	342,900	HHC506R.2	Belt	Std	51"Lx28"Wx51"H	675
852	1.109-126.0	4.0	3000	7.5	1725	208/3	25	Oil	342,900	HH406R.2	Belt	Std	51"Lx28"Wx51"H	665
853	1.109-127.0	4.0	3000	7.5	1725	230/1	37	Oil	342,900	HH406R.2	Belt	Std	51"Lx28"Wx51"H	665
854	1.109-128.0	4.0	3000	7.5	1725	230/3	25	Oil	342,900	HH406R.2	Belt	Std	51"Lx28"Wx51"H	665
855	1.109-129.0	4.0	3000	7.5	1725	460/3	14	Oil	342,900	HH406R.2	Belt	Std	51"Lx28"Wx51"H	665
856	1.109-130.0	4.0	3000	8.2	3450	575/3	11	Oil	342,900	HHC506R.2	Belt	Std	51"Lx28"Wx51"H	680
873	1.109-131.0	5.0	3000	10	1725	230/1	42	Oil	395,452	HH406R.2	Belt	Std	51"Lx28"Wx51"H	670
874	1.109-132.0	5.0	3000	10	1770	230/3	29	Oil	395,452	HH406R.2	Belt	Std	51"Lx28"Wx51"H	675

OPTIONS

PART NO.	DESCRIPTION
8.930-170.0	Auto Start/Stop Kit (Field Installed)*
8.930-172.0	Thermal Shutdown Kit (Field Installed)
8.930-171.0*	Time Delay Shutdown (Field Installed)*
8.717-764.0	8" Oil-Fired Draft Dampener (Oil-fired models only)
8.750-486.0	360° Pivot Reel, 100'
8.750-483.0	360° Pivot Reel, 200'
8.711-907.0	Pneumatic Wheel - 12 1/2" (one wheel only)
8.923-225.0	Detergent Bracket

* Note: Time Delay Shutdown and Auto Start/Stop cannot be combined on the same machine

Hot Water **ELECTRIC** Pressure Washers



900/1400 SERIES



The 900/1400 Series - Hotsy's innovative stationary models are packed with standard features! The most impressive is the programmable smart control automation. Safety is key with a pressure relief valve and locking lid and side panels around the belt and pulleys to keep users safe. These electric-powered washers are available in either LP or Natural Gas fired models. New models have the same footprint as previous generations, so users can feel confident about upgrading. Panels may be easily removed for access to the machine components for servicing. All models are ETL certified to the rigid UL-1776 safety standards. Features a Hotsy highly efficient Triplex pump. Equipped with a 50' hose.



MODEL	PART NO.	GPM	PSI	HP	MOTOR RPM	VOLT/PH	AMPS	FUEL	BTU/HR	PUMP MODEL	DRIVE	DIMENSIONS	SHIP WT (lbs)
921N	1.109-691.0	4.0	2300	6.2	3450	208/1	28	NG	364,835	HM4035R.3	Belt	47.5"Lx21"Wx51"H*	700
926N	1.109-692.0	4.0	2000	5	1800	575/3	7	NG	364,835	HM4035R.3	Belt	47.5"Lx21"Wx51"H*	660
942P	1.109-693.0	4.0	2000	5	1725	208/3	18	LP	360,997	HM4035R.3	Belt	47.5"Lx21"Wx51"H*	590
942N	1.109-694.0	4.0	2000	5	1725	208/3	18	NG	364,835	HM4035R.3	Belt	47.5"Lx21"Wx51"H*	655
943P	1.109-695.0	4.0	2000	5	1725	230/1	25	LP	360,997	HM4035R.3	Belt	47.5"Lx21"Wx51"H*	685
943N	1.109-696.0	4.0	2000	5	1725	230/1	25	NG	364,835	HM4035R.3	Belt	47.5"Lx21"Wx51"H*	685
944P	1.109-697.0	4.0	2000	5	1725	230/3	16	LP	360,997	HM4035R.3	Belt	47.5"Lx21"Wx51"H*	580
944N	1.109-698.0	4.0	2000	5	1725	230/3	16	NG	364,835	HM4035R.3	Belt	47.5"Lx21"Wx51"H*	680
945P	1.109-699.0	4.0	2000	5	1725	460/3	8	LP	360,997	HM4035R.3	Belt	47.5"Lx21"Wx51"H*	585
945N	1.109-700.0	4.0	2000	5	1725	460/3	8	NG	364,835	HM4035R.3	Belt	47.5"Lx21"Wx51"H*	585
1451N	1.109-701.0	4.0	3000	8.2	3450	208/1	42	NG	364,835	HM4035R.3	Belt	47.5"Lx21"Wx51"H*	730
1452P	1.109-702.0	4.0	3000	7.5	1725	208/3	24	LP	360,997	HM4035R.3	Belt	47.5"Lx21"Wx51"H*	625
1452N	1.109-703.0	4.0	3000	7.5	1725	208/3	24	NG	364,835	HM4035R.3	Belt	47.5"Lx21"Wx51"H*	625
1453P	1.109-704.0	4.0	3000	7.5	1725	230/1	34	LP	360,997	HM4035R.3	Belt	47.5"Lx21"Wx51"H*	735
1453N	1.109-705.0	4.0	3000	7.5	1725	230/1	34	NG	364,835	HM4035R.3	Belt	47.5"Lx21"Wx51"H*	735
1454P	1.109-706.0	4.0	3000	7.5	1725	230/3	24	LP	360,997	HM4035R.3	Belt	47.5"Lx21"Wx51"H*	625
1454N	1.109-707.0	4.0	3000	7.5	1725	230/3	24	NG	364,835	HM4035R.3	Belt	47.5"Lx21"Wx51"H*	700
1455P	1.109-708.0	4.0	3000	7.5	1725	460/3	12	LP	360,997	HM4035R.3	Belt	47.5"Lx21"Wx51"H*	630
1455N	1.109-709.0	4.0	3000	7.5	1725	460/3	12	NG	364,835	HM4035R.3	Belt	47.5"Lx21"Wx51"H*	780
1456N	1.109-710.0	4.0	3000	8.2	3450	575/3	10	NG	364,835	HM4035R.3	Belt	47.5"Lx21"Wx51"H*	621
1473P	1.109-711.0	5.0	3000	10	1725	230/1	42	LP	378,617	HM4035R.3	Belt	47.5"Lx21"Wx51"H*	735
1473N	1.109-713.0	5.0	3000	10	1725	230/1	42	NG	390,025	HM4035R.3	Belt	47.5"Lx21"Wx51"H*	735
1474P	1.109-712.0	5.0	3000	10	1770	230/3	29	LP	378,617	HH406R.2	Belt	47.5"Lx21"Wx51"H*	740
1474N	1.109-714.0	5.0	3000	10	1770	230/3	29	NG	390,025	HH406R.2	Belt	47.5"Lx21"Wx51"H*	740

* including connectors and flue outlet

OPTIONS

PART NO.	DESCRIPTION
8.916-989.0	Remote Station
8.916-988.0	Soap Solenoid and Switch
8.717-728.0	8" Natural Gas- or LP Gas-Fired Draft Diverter (Gas-fired models only)

1800 SERIES

- Natural Gas, Oil or optional LP-Fired
- Belt Drive with 7-Year Warranty
- Smart Relay Control provides control over run time, auto start/stop and shut down functionality



The **1800 Series** provides stationary cleaning with hot water indoors. The 7 models are electric-powered and natural gas, oil or optional LP gas-heated, using Hotsy's high-efficiency vertical hot water coil. The coil skin comes standard with stainless steel. The sleek cabinet has removeable side and front panels, making it easy for routine preventative maintenance and service. The Smart Relay allows the washer to be customized to individual needs, and is protected behind the front panel. This heavy-duty cleaning machine is ideal for use in manufacturing or even food processing facilities where hot water is needed for cleaning machinery and equipment indoors. All models are certified to the rigid UL-1776 safety standards and feature the highly efficient Hotsy Triplex pump. A pressure switch is a standard feature on all 1800 Series models. Equipped with a 50' hose.



MODEL	PART NO.	GPM	PSI	HP	VOLT/PH	AMPS	FUEL	BTU/HR	PUMP MODEL	DRIVE	DIMENSIONS	SHIP WT (lbs)
1812SS	1.109-660.0	6.0	2500	10	230/1	42	NG	558,050	HX9536L.2	Belt	51"Lx31"Wx53.25"H	1,020
1830SS	1.109-665.0	6.0	3000	15	230/3	35	Oil*	579,776	HX9536L.2	Belt	51"Lx31"Wx53.25"H	1,020
1832SS	1.109-662.0	6.0	3000	15	230/3	33	NG	558,050	HX9536L.2	Belt	51"Lx31"Wx53.25"H	1,020
1832SS-208	1.109-661.0	6.0	3000	15	208/3	36	NG	558,050	HX9536L.2	Belt	51"Lx31"Wx53.25"H	1,020
1833SS	1.109-666.0	6.0	3000	15	460/3	21	Oil*	579,776	HX9536L.2	Belt	51"Lx31"Wx53.25"H	1,020
1835SS	1.109-663.0	6.0	3000	15	460/3	19	NG	558,050	HX9536L.2	Belt	51"Lx31"Wx53.25"H	1,020
1836SS	1.109-664.0	6.0	3000	15	575/3	16	NG	558,050	HX9536L.2	Belt	51"Lx31"Wx53.25"H	1,020

SS=Stainless Steel

*Oil-Fired models are not supplied with a fuel tank.

OPTIONS

PART NO.	DESCRIPTION
8.916-989.0	Remote Station
8.916-988.0	Soap Solenoid and Switch

OPTIONS

PART NO.	DESCRIPTION
8.903-074.0	LP Conversion Kit (Factory Installed)
9.801-040.0	10" Natural Gas or LP Gas Draft Diverter

5700/5800 SERIES

- Oil, Natural Gas or optional LP-Fired
- Belt Drive Pump with 7-Year Warranty
- Smart Relay Control provides control over run time, auto start/stop and shut down functionality



The **5700 and 5800 Series** produces a powerful punch and is ideal for wash bay installations. With its 20 HP Baldor motor driving the incomparable Hotsy Triplex Pump with NESTechnology with U-Seals and a vertical banded belt, the 5700 and 5800 Series delivers cleaning power up to 9.5 GPM and 3000 PSI. Has a sleek cabinet with removeable panels for easy access for maintenance. A removeable control panel provides access to the adjustable temperature control and the Smart Relay for secured control of operating positions. Remote ready for wash bay installations. All models are stationary and certified to the rigid UL-1776 safety standards. Equipped with a 50' hose.



MODEL	PART NO.	GPM	PSI	HP	VOLT/PH	AMPS	FUEL	BTU/HR	PUMP MODEL	HOSE	SHIP WT
5730SS	1.109-658.0	8.0	3000	20	230/3	44	Oil*	768,000	HX9536L.2	50'	1,471
5732SS-208	1.109-654.0	8.0	3000	20	208/3	55	NG	720,450	HX9536L.2	50'	1,471
5732SS	1.109-655.0	8.0	3000	20	230/3	42	NG	720,450	HX9536L.2	50'	1,471
5733SS	1.109-659.0	8.0	3000	20	460/3	23	Oil*	768,000	HX9536L.2	50'	1,471
5735SS	1.109-656.0	8.0	3000	20	460/3	21	NG	720,450	HX9536L.2	50'	1,471
5736SS	1.109-657.0	8.0	3000	20	575/3	16	NG	720,450	HX9536L.2	50'	1,471
5832SS	1.109-651.0	9.5	2500	20	230/3	42	NG	939,890	HX1036L.2	50'	1,471
5832SS-208	1.109-650.0	9.5	2500	20	208/3	48	NG	939,890	HX1036L.2	50'	1,471
5835SS	1.109-652.0	9.5	2500	20	460/3	21	NG	939,890	HX1036L.2	50'	1,461
5836SS	1.109-653.0	9.5	2500	20	575/3	16	NG	939,890	HX1036L.2	50'	1,471

SS=Stainless Steel

Dimensions: 51"L x 31"W x 63.4"H

*Oil-Fired models are not supplied with a fuel tank.

OPTIONS

PART NO.	DESCRIPTION
8.916-916.0	LP Conversion Kit, 5700 (Factory Installed)
8.916-915.0	LP Conversion Kit, 5800 (Factory Installed)

OPTIONS

PART NO.	DESCRIPTION
8.916-989.0	Remote Station
8.916-988.0	Soap Solenoid and Switch
8.717-730.0	12" Natural Gas or LP-Gas Draft Diverter

GAS-ENGINE SERIES

DIRECT-DRIVE

- Oil-Fired
- 12 Volt DC
- Direct Drive
- 3 Battery-less Models
- 2 Electric-Start Models
- 7-Year Pump Warranty



871SS



965SS



1065SSE

The Gas Engine Series consists of the most compact and portable hot water pressure washers on the market. Powered by reliable gasoline engines, all you need is water and you can clean anywhere anytime. The five models offer a broad range of cleaning power, from 3.0 to 4.0 GPM and from 2400 to 3500 PSI. All models feature Hotsy's highly efficient Triplex pump backed by Hotsy's 7-year pump warranty and all are ETL safety certified. All models are equipped with a standard pressure switch and 50' hose.



MODEL	PART NO.	GPM	PSI	ENGINE / MODEL	CC's	BURNER	BTU/HR	PUMP MODEL	DRIVE	PORTABILITY	DIMENSIONS	SHIP WT (lbs)
871SS*	1.110-014.0	3.0	2400	Subaru EX21	211	12V DC	248,500	HG3030G.1	Direct	Std	43"Lx27"Wx39"H	400
965SS*	1.110-015.0	3.0	3000	Honda GX270	270	12V DC	248,500	HG3035G1.1	Direct	Std	47"Lx31"Wx41"H	445
1065SS*	1.110-010.0	3.5	3000	Honda GX340	389	12V DC	309,900	HS3540G.3	Direct	Std	47"Lx31"Wx45"H	495
1065SSE†	1.110-011.0	3.5	3000	Honda GX340	389	12V DC	309,900	HS3540G.3	Direct	Std	47"Lx31"Wx45"H	510
1075SSE†	1.110-012.0	4.0	3500	Honda GX390	389	12V DC	309,900	HS4040G.3	Direct	Std	47"Lx31"Wx45"H	520

* Battery not required † 12V battery required, but not supplied E = Electric-start engine

GAS-ENGINE SERIES

BELT-DRIVE

- Oil-Fired
- 12 Volt DC
- Belt Drive
- 2 Electric-Start Models
- 7-Year Pump Warranty



1075BE (Shown with optional caster wheel kit)



965B (Shown with optional pneumatic tires)



1080BE (Shown with optional stainless steel coil wrap and skid rails)

The belt-drive versions of the Gas Engine Series provide versatility with the roll cage design. Designed to fit the needs of the end-user, this versatile hot water washer converts easily to a skid unit, portable with wheels or a wheel/caster kit, or can be mounted on a trailer. Powered by reliable gasoline engines, the three models offer a broad range of cleaning power, from 3.0 to 4.6 GPM and from 3000 to 3500 PSI. All models feature the Hotsy Triplex pump backed by Hotsy's 7-year pump warranty and all are ETL safety certified. All models are equipped with a standard pressure switch and 50' hose.



MODEL	PART NO.	GPM	PSI	ENGINE / MODEL	CC's	BURNER	BTU/HR	PUMP MODEL	DRIVE	PORTABILITY	DIMENSIONS	SHIP WT (lbs)
965B*	1.110-565.0	3.0	3000	Honda GX270	270	12V DC	248,500	HD3030L.1	Belt	Optional	42"Lx27.5"Wx39"H	590
1075BE†	1.110-566.0	4.0	3500	Honda GX390	389	12V DC	385,800	HM4035L.3	Belt	Optional	42"Lx27.5"Wx39"H	625
1080BE†	1.110-567.0	4.6	3500	Briggs VAN 16	479	12V DC	385,800	HM4035L.3	Belt	Optional	42"Lx27.5"Wx39"H	665

* Battery not required † 12V battery required, but not supplied E = Electric-start engine B = Belt Drive

OPTIONS

PART NO.	DESCRIPTION
8.916-172.0	Float Tank Kit (includes high pressure detergent kit), 1075BE & 1080BE models
8.916-173.0	Float Tank Kit (includes high pressure detergent kit) 965B model
8.931-259.0	Skid Rail Kit (Field Installed)- adds 3.875" to height
8.931-260.0	Caster Kit - 2 casters / 2 wheels (Field Installed) - adds 7.5" to height
8.931-261.0	Pneumatic Tire Kit with Handle Bar (Field Installed) - adds 10" to width, 6" to height
8.916-175.0	High Pressure Detergent Kit, 1075BE & 1080BE models (to be used with a remote water tank)
8.916-174.0	High Pressure Detergent Kit, 965B models (to be used with a remote water tank)
8.915-274.0	Stainless Steel Coil Wrap (Field Installed)

Hot Water **GAS ENGINE** Pressure Washers



1200 SERIES and Model 5645

- Gas-Powered
- Oil-Fired
- Belt Drive
- Electric Start
- 7-Year Pump Warranty



1260SS



1270SS Shown
with optional
Portage Kit



5645

The **1200 Series** delivers some serious on-site, hot water cleaning capability of up to 6 GPM and 4000 PSI. Rugged gasoline engines all have electric start. Six models come with a 2000W generator. The self-contained cleaning units are built to hold up under the toughest of conditions. All feature the Hotsy Triplex pump, with its 7-year warranty and ETL safety certification (CSA-Certified for non-generator models). All 1200 Series models are equipped with a standard flow switch and 50' hose.



MODEL	PART NO.	GPM	PSI	ENGINE / MODEL	CC's	BURNER	BTU/HR	PUMP MODEL	DRIVE	PORTABILITY	DIMENSIONS	SHIP WT (lbs)
1260SS	1.110-533.0	4.5	3000	Briggs VAN 16	479	12V DC	385,800	HHC506R.2	Belt	Optional	45"Lx33"Wx52"H	745
1260SSG*	1.110-535.0	4.5	3000	Briggs VAN 16	479	120V AC	398,400	HHC506R.2	Belt	Optional	45"Lx33"Wx52"H	830
1270SS	1.110-557.0	4.5	4000	Honda GX630	688	12V DC	385,800	HHC930R.1	Belt	Optional	45"Lx33"Wx52"H	855
1270SSG*	1.110-536.0	4.5	4000	Honda GX630	688	120V AC	398,400	HHC930R.1	Belt	Optional	45"Lx33"Wx52"H	870
1280SS	1.110-558.0	5.1	3500	Honda GX630	688	12V DC	385,800	HX8043R.2	Belt	Optional	45"Lx33"Wx52"H	760
1280SSG*	1.110-537.0	5.1	3500	Honda GX630	688	120V AC	398,400	HX8043R.2	Belt	Optional	45"Lx33"Wx52"H	750
1285SS	1.110-043.0	5.1	3500	Briggs VAN 21	627	12V DC	385,800	HX8043R.2	Belt	Optional	45"Lx33"Wx52"H	840
1285SSG*	1.110-044.0	5.1	3500	Briggs VAN 21	627	120V AC	398,400	HX8043R.2	Belt	Optional	45"Lx33"Wx52"H	895
1290SS	1.110-538.0	5.6	3000	Honda GX630	688	12V DC	385,800	HX8043R.2	Belt	Optional	45"Lx33"Wx52"H	744
1290SSG*	1.110-539.0	5.6	3000	Honda GX630	688	120V AC	398,400	HX8043R.2	Belt	Optional	45"Lx33"Wx52"H	905
5645*	1.110-556.0	6.0	3000	Honda GX660	688	120V AC	528,000	HHC800.1	Belt	Optional	61"Lx32"Wx50"H	1126

* Models include a 2000W Generator 12V battery is required for all models, but is not supplied

SUPER DUTY OPTION KIT

PART NO.	DESCRIPTION
8.903-081.0	1285SS / 1285SSG

General Description-Modifications to existing equipment (Super Duty Option):
 Remove Float Tank. Replace Flow Switch with HD Pressure Switch. Replace unloader with VB80. Remove inlet detergent injector. Add Hot Seals to pump. Replace existing coil with stainless steel wrapped coil with base plate. Coil wound as a gas coil to reduce soot build up.

OPTION

PART NO.	DESCRIPTION
8.903-025.0	Portage Kit (all models except 5645)

Super Skid HSS SERIES

- Diesel-Powered
- Diesel-Fired
- Belt Drive
- Electric-Start
- 7-Year Pump Warranty



The Super Skid HSS Series is by far, the largest, most powerful of Hotsy's hot water pressure washers. All models come standard with the reliable Hotsy triplex belt-driven high-pressure pump. The Super Skid HSS series models are rated for continuous use and are ideal for heavy duty, on-site cleaning where electricity is not available. Models are powered by a Kohler engine with electric start and all feature a 3/4-inch Schedule 80 heating coil with stainless steel skin and 5-year warranty. A flow switch is a standard feature on all HSS Super Skid models.



MODEL	PART NO.	GPM	PSI	ENGINE / MODEL	CC's	BURNER	BTU/HR	PUMP MODEL	HOSE	DIMENSIONS	SHIP WT (lbs)
HSS-503089E	1.110-546.0	5.0	3000	Kohler KDW702	686	120V AC	620,000	HX5843R.2	50'-3/8"	66"Lx37"Wx53"H	1790
HSS-603289E	1.110-547.0	6.5	3200	Kohler KDW1003	1028	120V AC	620,000	HX5843R.2	50'-3/8"	66"Lx37"Wx53"H	1825
HSS-803089E	1.110-548.0	8.0	3000	Kohler KDW1003	1028	120V AC	744,000	HX5843R.2	50'-1/2"	73"Lx37"Wx64"H	2165
HSS-102589E	1.110-545.0	9.5	2500	Kohler KDW1003	1028	120V AC	920,000	HX1036R.2	50'-1/2"	73"Lx37"Wx64"H	2200

All Models are Electric Start and include a 2000W Generator. 12V battery is required for all models, but is not supplied

Replacement HSS Models Coming Early 2015:

MODEL	PART NO.	GPM	PSI	ENGINE / MODEL	CC's	BURNER	BTU/HR	PUMP MODEL	HOSE	DIMENSIONS	SHIP WT (lbs)
HSS-503069E	1.110-604.0	5.0	3000	Kubota Z602-E4B	599	12V DC	620,000	TBD	50'-3/8"	73"Lx37"Wx64"H	TBD
HSS-653569E	1.110-605.0	6.5	3500	Kubota D1105-E4B	1123	12V DC	620,000	TBD	50'-3/8"	73"Lx37"Wx64"H	TBD
HSS-803069E	1.110-606.0	8.0	3000	Kubota D1105-E4B	1028	12V DC	920,000	TBD	50'-1/2"	73"Lx37"Wx64"H	TBD
HSS-952569E	1.110-607.0	9.5	2500	Kubota D1105-E4B	1028	12V DC	920,000	TBD	50'-1/2"	73"Lx37"Wx64"H	TBD

12V battery is required for all models, but is not supplied

OPTIONS

PART NO.	DESCRIPTION
8.923-164.0	Dual Gun Kit (Field installed)
8.923-125.0	Steam Kit (Field installed)
8.923-124.0	Float Tank Kit (includes high pressure detergent kit (Field installed)
TBD	Super Duty Option (Factory installed)

HWE SERIES

All Electric Models

- All Electric
- Belt Drive
- Auto/Start Stop
- Stainless Steel Coil
- 7-Year Pump Warranty



The HWE Series is powered and heated by electricity, making it ideal for indoor use. It's a quiet machine with no fumes, making it ideal for food service and in-plant cleaning. Water is heated in a stainless steel heating coil, immersed in a tank of water solution, allowing for instant hot water once you pull the trigger. The heating elements do not come in contact with the pressurized water, which results in less maintenance and minimizes scale build up. The HWE features a Baldor motor, which drives a belt-drive Hotsy Triplex pump, with 7-year warranty, and an insulated variable pressure wand. ETL certified. Float switch is standard on the HWE Series. All models equipped with a 50' hose.



MODEL	PART NO.	GPM	PSI	HP	MOTOR	AMPS	VOLT/PH	KvA HOUR	BTU/HR	PUMP MODEL	DRIVE	DIMENSIONS	SHIP WT (lbs)	LIST PRICE
HWE-402009C	1.109-646.0	4.0	2000	6.2	Baldor	55.2	460/3	40.5	138,308	HH306R.2	Belt	34"Lx25"Wx52"H	620	
HWE-353009C	1.109-647.0	3.5	3000	7.5	Baldor	59	460/3	40.5	138,308	HH306R.2	Belt	34"Lx25"Wx52"H	640	

OPTIONS

PART NO.	DESCRIPTION
8.903-042.0	Stainless Steel Washer Wrap 1700 Series (Factory installed)*
8.725-157.0	Option, Time Delay Shutdown HWE-4020C (Factory installed)**
8.725-158.0	Option, Time Delay Shutdown HWE-4030C (Factory installed)**
8.941-506.0	460V / 3PH Heating Module Only (unbranded)

*See page 16 in the Specials portion of the price list for stainless steel and other configured options.

** Note: Time Delay Shutdown and Auto Start/Stop cannot be combined on the same machine

Hot Water HEATING MODULES and TRAILER



9400 SERIES Heating Modules

The **9400 Series** heating modules give customers the flexibility to "convert" a cold water pressure washer into a hot water unit. By attaching the heating module to a cold water pressure washer the pressurized water is now heated to produce all the benefits of hot water cleaning. The four models use fuel oil, diesel or natural gas to heat the water using Hotsy's high-efficiency, vertical heating coil. All models are equipped with a flow switch to control the burner.



Model 9462



Model 9452



MODEL	PART NO.	PSI (Max)	GPM (Max)	GPM (Min)	VOLT/PH	BTU/HOUR	AMP	FUEL	DIMENSIONS	SHIP WT (lbs)
9450	1.103-905.0	3200	10	6	115/1	700,000	8	Oil-Fired	32.5"Lx25"Wx50.5"H	525
9452	1.103-906.0	3200	10	6	115/1	540,000	1	Natural-Gas-Fired	32.5"Lx25"Wx50.5"H	500
9460	1.103-907.0	3200	10	6	115/1	920,000	8	Oil-Fired	40.5"Lx32"Wx65"H	920
9462	1.103-908.0	3200	10	6	115/1	920,000	1	Natural-Gas-Fired	40.5"Lx32"Wx65"H	935

OPTIONS

PART NO.	DESCRIPTION
8.903-076.0	Natural-Gas to LP Conversion for Model 9452 (Factory Installed)
8.903-075.0	Natural-Gas to LP Conversion for Model 9462 (Factory Installed)
9.801-040.0	10" Natural Gas-Fired Draft Diverter for Model 9452
8.717-730.0	12" Natural Gas-Fired Draft Diverter for Model 9462

Fuel-burner types available:

- Diesel ■ Kerosene ■ Home Heating Oil
- Natural Gas ■ LP Gas (Optional)

Trail Blazer TRAILER

- 200 Gallon Water Tank
- Single axle rated to 3500 pounds
- Swing away hinged tongue



Shown with 1080BE and optional accessories

The **Trail Blazer** is Hotsy's affordable trailer solution that provides mobile cleaning anywhere. Axle assembly with leaf-spring suspension is rated at 3,500 lbs. The heavy duty-chassis features a swing-away hinge with swivel jack tongue assembly. The 200 gallon water tank features a float valve and 7-inch access port. 15-inch white spoke wheel assembly. Idle axle (no brakes) is the standard configuration.

Select a trailer and add one of these pressure washer models:

965B
1075BE
1075SSE
1080BE
1200 Series

MODEL	PART NO.	LOAD CAPACITY	WATER TANK CAPACITY	AXLE	WHEELS	JACK	JACK CAPACITY	BALL COUPLER	SAFETY CHAINS	LIGHTING
TRB-3500	1.103-818.0	3000 lbs	200 gal	Single 3500 lbs	15" White Spoke Wheels ST205/75D15 Tires	Swivel Wheel w/Caster Foot	1000 lbs	2"	Dual 5/16"	Recessed Lights are DOT approved

Trailer Dimensions 136" L x 66" W x 52" H

Trailer Weight: 543 lbs.

Shipping Weight: 1043 lbs. (does not include pressure washer)

OPTIONS (FACTORY INSTALLED)

PART NO.	DESCRIPTION
8.917-397.0	Brakes, Electric
8.917-398.0	Brakes, Hydraulic
8.917-553.0	Break-Away (available w/Electric Brakes)
8.917-554.0	High Pressure Hose Reel
8.917-555.0	Low Pressure Hose Reel
8.917-556.0	Saddle Box Kit, set of two
8.917-557.0	Rock Guard Kit
8.917-583.0	Chrome Wheel Rims

OPTIONS (FACTORY INSTALLED)

PART NO.	DESCRIPTION
8.917-290.0	Assembly Mounting (for 1200 Series)*
8.917-291.0	Assembly Mounting (for 965B, 1075BE, 1080BE Models)*
8.917-471.0	Assembly Mounting (for 1260SS/SSG Models)*
8.917-472.0	Assembly Mounting (for 1075SSE Model)*

*Required when purchasing a pressure washer and trailer package; NOT available for trailer only purchases

KITS (FIELD INSTALLED)

PART NO.	DESCRIPTION
8.917-559.0	Rock Guard Kit
8.917-558.0	Saddle Box Kit - single box only
8.917-560.0	Utility Rack Kit (150 lb. load capacity)

*Flat \$300 freight charge applies to **all** trailer purchases (trailer only as well as a configured trailers).

BD SERIES

BELT DRIVE


BD Series shown in large cage (4-wheel) version. Small cage 2-wheel version also available.

The **BD Series** is the most rugged cold water pressure washer on the market with its all-steel frame and cage, Hotsy belt-drive, triplex pump and cleaning power of up to 5000 PSI. Four gas models make up what is Hotsy's most durable cold water line-up ever. All models equipped with a 50' hose.

- Honda or Vanguard engine
- Small & Large Roll Cage design
- Totally enclosed belt guard
- 13" tubed pneumatic tires for easy handling
- Plated steel high-pressure wand w/ side handle
- ETL certified to UL-1776 safety standards



MODEL	PART NO.	GPM	PSI	ENGINE / MODEL	CC's	PUMP MODEL	FRAME	DIMENSIONS	NO. WHEELS	SHIP WT (lbs)
BD-373539	1.107-021.0	3.7	3500	Honda GX390	389	HM4035R.2	Small Cage	42"Lx26"Wx30"H	2	275
BD-404029	1.107-022.0	4.0	4000	Briggs VAN 16	479	HHC930R.1	Large Cage	46"Lx30"Wx36"H	4	360
BD-405039E*	1.107-023.0	4.0	5000	Honda GX630	688	HH5050R	Large Cage	46"Lx30"Wx36"H	4	417
BD-455039E*	1.107-024.0	4.5	5000	Honda GX660	688	HH5050R	Large Cage	46"Lx30"Wx36"H	4	430
BD-343089E*	1.107-083.0	3.4	3000	Kohler KD420 Diesel	442	HM3540R.2	Large Cage	46"Lx30"Wx36"H	4	410

*E = Electric Start

OPTIONS

PART NO.	DESCRIPTION
8.904-109.0	E-Zee Hose Reel Kit* 100' (small cage)
8.904-110.0	E-Zee Hose Reel Kit* 100' (large cage)

*Kit includes hose reel and mounting hardware

OPTIONS

PART NO.	DESCRIPTION
8.904-113.0	5000 PSI Hose Reel Kit* (large cage)
8.904-115.0	5000 PSI Dual Hose Reel Kit,*† (large cage)

†Includes garden hose reel and high-pressure hose reel

BX/BXA SERIES

BELT DRIVE


BX Series shown with optional hose reel & mounting kit.

The **BX/BXA Series** is the similarly rugged, but more compact, line of belt-drive cold water pressure washers. Powered by Honda engines, the BX/BXA series delivers cleaning power up to 3500 PSI and an all-steel frame protected by a durable powder coat finish. The Hotsy triplex pumps carry a 7-year warranty. Equipped with a 50' hose.

- Honda engines
- Steel & Aluminum frame
- Totally enclosed belt guard
- 13" tubed pneumatic tires for easy handling
- Insulated steel high-pressure wand w/ side handle
- ETL certified to UL-1776 safety standards

Note: Detergent Injector Sold Separately on BXA models



MODEL	PART NO.	GPM	PSI	ENGINE	CC's	START	PUMP MODEL	FRAME	DIMENSIONS	DRIVE	SHIP WT (lbs)
BX-282039	1.107-026.0	2.8	2000	Honda GX160	163	Recoil	HD3030R.1	Small Chassis	37"Lx21"Wx24"H	Belt	152
BX-373539	1.107-028.0	3.7	3500	Honda GX390	389	Recoil	HM4035R.2	Large Chassis	45"Lx26"Wx24"H	Belt	240
BXA-252739	1.107-120.0	2.5	2700	Honda GX200	196	Recoil	HD3030R.1	Aluminum	45.9"Lx26"Wx39.7"H	Belt	196
BXA-373539	1.107-121.0	3.7	3500	Honda GX390	389	Recoil	HM4035R.3	Aluminum	45.9"Lx27"Wx40.6"H	Belt	249

OPTIONS

PART NO.	DESCRIPTION
8.929-062.0	Detergent Injector (up to 3 GPM)**
9.802-225.0	Detergent Injector (over 3 GPM)**

** BXA models only

OPTIONS

PART NO.	DESCRIPTION
8.723-636.0	Detergent nozzle**
8.904-103.0	EZ Hose Reel Kit 100' (incl. reel & mounting hardware)*

* BX models only

BUNDLE PACKS Mix & Match any combination of the BXA-252739 & BXA-373539 **3 PK = SAVE \$300; 5 PK = SAVE \$625; 10 PK = SAVE \$1,400**

DB SERIES

DIRECT DRIVE

DB Series shown with optional hose reel & mounting kit.



The **DB Series** is the most compact, affordable alternative, in the cold water line featuring a direct-drive triplex pump. All four models are powered by reliable Honda engines. Light-weight design and tubed pneumatic tires make for easy maneuvering.

- Honda GX engines
- Steel frame
- 10" tubed pneumatic tires for easy handling
- Protected by a powder coat finish
- Insulated, 2-piece steel high-pressure wand
- ETL certified to UL-1776 safety standards



MODEL	PART NO.	GPM	PSI	ENGINE / MODEL	CC's	PUMP MODEL	DRIVE	DIMENSIONS	HOSE	SHIP WT (lbs)
DB-232439	1.107-031.0	2.3	2400	Honda GX160	163	HG2530G.1	Direct	35"Lx21"Wx24"H	50'	140
DB-252739	1.107-032.0	2.5	2700	Honda GX200	196	HG2530G.1	Direct	35"Lx21"Wx24"H	50'	145
DB-303039	1.107-033.0	3.0	3000	Honda GX270	270	HG3035G.1.1	Direct	35"Lx21"Wx24"H	50'	175
DB-354039	1.107-222.0	3.5	4000	Honda GX390	390	HS3540G.3	Direct	35"Lx21"Wx24"H	50'	179
DB-383539	1.107-034.0	3.8	3500	Honda GX390	390	HS4040G.2	Direct	35"Lx21"Wx24"H	50'	179

OPTIONS

PART NO.	DESCRIPTION
8.904-105.0	EZ Hose Reel Kit 100' (incl. reel & mounting hardware)

Cold Water **GAS ENGINE** Pressure Washers



DBA SERIES

DIRECT DRIVE



The **DBA Series** are direct-drive cold water pressure washers with corrosion resistant aluminum frame, making them lightweight and easy to load and unload. Powered by Honda GX engines, the DBA series delivers cleaning power up to 4000 PSI. The commercial duty pump carry a 7-year warranty. Models equipped with a 50' hose.



- Honda GX engines
- Aluminum frame with fold down handle
- Thermal pump protector
- Tubed pneumatic tires for easy handling
- Hose and gun hanger for safe storage
- ETL certified to UL-1776 safety standards

Note: Detergent Injector Sold Separately

MODEL	PART NO.	GPM	PSI	ENGINE / MODEL	CC's	START	PUMP MODEL	DRIVE	DIMENSIONS	HOSE	SHIP WT (lbs)
DBA-252739	1.107-117.0	2.5	2700	Honda GX200	196	Recoil	HG2530G.1	Direct	39.3"Lx22.5"Wx39.6"H	50'	125
DBA-303039	1.107-118.0	3.0	3000	Honda GX270	270	Recoil	HG3035G1.1	Direct	39.3"Lx22.5"Wx39.6"H	50'	148
DBA-354039	1.107-226.0	3.5	4000	Honda GX390	390	Recoil	HS3540G.3	Direct	41"Lx23"Wx40"H	50'	167
DBA-383539	1.107-119.0	3.8	3500	Honda GX390	390	Recoil	HG4040G.2	Direct	40.8"Lx22.5"Wx39.6"H	50'	172

OPTIONS

PART NO.	DESCRIPTION
8.929-062.0	Detergent Injector (up to 3 GPM)
9.802-225.0	Detergent Injector (over 3 GPM)

OPTIONS

PART NO.	DESCRIPTION
8.723-636.0	Detergent nozzle

DA SERIES

DIRECT DRIVE



The **DA Series** is a rugged, yet compact, line of direct-drive cold water pressure washers. Powered by Honda GX or GC engines, the DA series delivers cleaning power up to 4000 PSI with an all-welded chassis protected with all-weather, epoxy powder coat finish. The Hotsy triplex pumps carry a 7-year warranty.



- Honda GX / GC engines
- All welded chassis
- Thermal pump protector
- Tubed pneumatic tires for easy handling
- Hose and gun hanger for safe storage
- ETL certified to UL-1776 safety standards

MODEL	PART NO.	GPM	PSI	ENGINE / MODEL	CC's	START	PUMP MODEL	DRIVE	DIMENSIONS	HOSE	SHIP WT (lbs)
DA-232336	1.107-097.0	2.3	2300	Honda GC160	160	Recoil	COMET BXD	Direct	23"Lx22"Wx25"H	25'	73
DA-232337	1.107-098.0	2.3	2300	Honda GC160	160	Recoil	Legacy Axial	Direct	23"Lx22"Wx25"H	25'	72
DA-252739	1.107-100.0	2.5	2700	Honda GX200	196	Recoil	HG2530G1.1	Direct	23"Lx22"Wx25"H	50'	99
DA-354039	1.107-218.0	3.5	4000	Honda GX390	390	Recoil	HS3540G.3	Direct	36.5"Lx23.5"Wx30.5"H	50'	166
DA-383539	1.107-102.0	3.8	3500	Honda GX390	390	Recoil	HS4040G.2	Direct	36.5"Lx23.5"Wx30.5"H	50'	166

PALLET PRICING

MODEL	PART NO.	DESCRIPTION
DA-232336	8.917-667.0	Pallet of 8
DA-232337	8.917-668.0	Pallet of 8
DA-252739	8.917-670.0	Pallet of 8
DA-354039	8.921-612.0	Pallet of 2
DA-383539	8.917-672.0	Pallet of 2

PALLET COMBINATIONS:

Qty of 5 - DA-232337 and
Qty of 3 - DA-252739
PART NO. 8.917-673.0

Qty of 5 - DA-232336 and
Qty of 3 - DA-252739
PART NO. 8.917-674.0

Cold Water **GAS ENGINE** Pressure Washers



COLD WATER PRESSURE WASHER SKID

UTV BUDDY

Gasoline-Powered

DIRECT DRIVE



The **UTV Buddy** is our skid style model of the cold water gasoline-powered line, delivering cleaning capability of 2700 PSI. The UTV Buddy fits most utility vehicles and pick-up trucks, and is driven by a Subaru engine and features a reliable direct-drive triplex pump and is ETL safety certified.



- Subaru 6 HP engine
- Direct-drive high-pressure pump
- 65-gallon water tank
- All steel frame
- Convenient fork lift openings
- Recoil start

MODEL	PART NO.	GPM	PSI	ENGINE / MODEL	CC's	PUMP MODEL	DRIVE	DIMENSIONS	HOSE	SHIP WT (lbs)
DGB-252719	1.107-232.0	2.5	2700	Subaru EX17	169	HG2530G	Direct	39.942"Lx47.75"Wx35.38"H	50'	490

OPTIONS

PART NO.	DESCRIPTION
8.923-105.0	Rubber Foot Kit
8.923-106.0	Lifting Eye Kit

OPTIONS

PART NO.	DESCRIPTION
8.923-107.0	Inline Filter Kit
8.923-108.0	3 Way Valve Kit

HAND-HELD COLD WATER PRESSURE WASHER - GAS ENGINE

HC SERIES

Gasoline-Powered

DIRECT DRIVE



The **HC Series** is the hand-held model of the gasoline-powered line, delivering cleaning capability up to 2400 PSI. The HC is driven by a Honda engine and features a reliable direct-drive triplex pump and is ETL safety certified.



- Honda engine
- Direct-drive high-pressure pump
- Cleaning power up to 2400 PSI
- Weighs 80 lbs.
- Convenient carrying handle

MODEL	PART NO.	GPM	PSI	ENGINE / MODEL	CC's	PUMP MODEL	DRIVE	DIMENSIONS	HOSE	SHIP WT (lbs)
HC-232336	1.107-035.0	2.3	2300	Honda GC160	160	Legacy Axial	Direct	20"Lx16"Wx17"H	25'	74
HC-232439	1.107-036.0	2.3	2400	Honda GX160	163	HG2530G.1	Direct	20"Lx16"Wx17"H	25'	95

Cold Water **ELECTRIC** Pressure Washers



1700 SERIES BELT DRIVE



Shown with optional stainless steel cabinet

The **1700 Series** offers the most reliable stationary, electric-powered, cold water pressure washer featuring a Hotsy belt-drive, triplex pump with 7-year warranty, insulated variable pressure wand and ETL safety certification. All models equipped with a 50' hose

- Baldor electric motor, 2-10 HP
- Hotsy pump with 7-year warranty
- Downstream detergent injector
- Insulated SS variable pressure wand
- Hot Water Seal Kit standard
- Option-ready for time delay shutdown or automatic stop-start.



MODEL	PART NO.	GPM	PSI	HP	VOLT/PH	AMPS	PUMP MODEL	DRIVE	PORTABILITY	DIMENSIONS	SHIP WT (lbs)
1710	1.106-511.0	2.75	1000	2	120/1	20	HD3030R.1	Belt	Optional	31"Lx21"Wx16"H	200
1720	1.106-512.0	3.9	2000	6	230/1	28	HH306R.2	Belt	Optional	31"Lx21"Wx16"H	275
1722	1.106-513.0	3.9	2000	6	208/1	30	HH306R.2	Belt	Optional	31"Lx21"Wx16"H	240
1723	1.106-514.0	3.9	2000	6	208/3	16	HH306R.2	Belt	Optional	31"Lx21"Wx16"H	250
1724	1.106-515.0	3.9	2000	6	230/3	14.4	HH306R.2	Belt	Optional	31"Lx21"Wx16"H	250
1725	1.106-516.0	3.9	2000	6	460/3	7.2	HH306R.2	Belt	Optional	31"Lx21"Wx16"H	250
1743	1.106-529.0	4.76	3000	10	208/3	31.3	HHC506R.2	Belt	Optional	31"Lx21"Wx16"H	302
1744	1.106-530.0	4.76	3000	10	230/3	26.8	HHC506R.2	Belt	Optional	31"Lx21"Wx16"H	300
1745	1.106-531.0	4.76	3000	10	460/3	13.5	HHC506R.2	Belt	Optional	31"Lx21"Wx16"H	315
1753	1.106-534.0	5.93	2500	10	208/3	31.3	HHC950R.1	Belt	Optional	31"Lx21"Wx16"H	320
1754	1.106-535.0	5.93	2500	10	230/3	26.8	HHC950R.1	Belt	Optional	31"Lx21"Wx16"H	310
1755	1.106-536.0	5.93	2500	10	460/3	13.5	HHC950R.1	Belt	Optional	31"Lx21"Wx16"H	310

OPTIONS 1700 SERIES

PART NO.	DESCRIPTION
9.801-031.0	Kit, 1700 Wheel w/Chemical Rack (black)
9.904-527.0	Kit, 1700 Wheel w/Chemical Rack - Stainless Steel
9.801-033.0	Kit, 1700 Wall Mount
9.801-034.0	Kit, 1700 Floor Stand, Tall (20 3/4"W x 29"D x 36"H)
9.801-035.0	Kit, Caster Wheels for 1700 Floor Stand
9.903-039.0	Kit, Hose Reel w/Bracket for 1700 Stand & Wall Mount Kits
9.903-040.0	Kit, 1700 Floor Stand, Short (20 3/4"W x 29"D x 24"H)
9.903-043.0	Kit, 1700 Wall Mount, Stainless Steel
9.903-041.0	Time Delay Shut Down, For 172x, 173x & 174x Models (Factory Installed)*
9.903-045.0	Time Delay Shut Down for 1710 (Factory Installed)*
9.903-044.0	Time Delay Shut Down for 175x Models (Factory Installed)*
9.903-042.0	Stainless Steel Base & Cover, 1700 Series (Factory Installed)
9.903-047.0	Automatic Stop/Start for 1710 & 172x Models (Factory Installed)
9.903-048.0	Automatic Stop/Start for 175x Models (Factory Installed)
9.903-046.0	Automatic Stop/Start for 173x & 174x Models (Factory Installed)
9.903-617.0	Kit, 1700 Floor Stand, Tall, Stainless Steel
9.903-521.0	Kit, Hose Reel for Wheel Kit 100 ft. (excludes hose)

* Note: Time Delay Shutdown and Auto Start/Stop cannot be combined on the same machine



1700 Series shown with optional hose reel kit, (PN 9.903-039.0), Tall Floor Stand (PN 9.801-034.0), caster wheel kit (PN 9.801-035.0) and stainless steel base and cover (PN 9.903-042.0).

Model 1710 shown with optional wheel kit and chemical rack (PN 9.801-031.0). Note - this is not the short stand.



CWC SERIES BELT DRIVE



The **CWC Series** is a completely self-contained stationary, electric-powered, cold water pressure washer with removable front panels for easy service access, programmable smart control and ETL safety certification. All models equipped with a 50' hose

- Vertical tensioned belt
- Large frame Hotsy pump with 7-year warranty
- Upstream detergent injector
- Remote ready for wash bays

■ Ideal for the food industry since hot water can be used

■ Smart Relay Control provides control over run time, auto start/stop and shut down functionality

MODEL	PART NO.	GPM	PSI	HP	MOTOR RPM	VOLT/PH	AMP	PUMP MODEL	HOSE	SHIP WT (lbs)
CWC-53	1.106-572.0	4.0	3000	7.5	1725	230/1	36	HH406R.1	50'	340
CWC-54	1.106-573.0	4.0	3000	7.5	1725	230/3	23	HH406R.1	50'	340
CWC-55	1.106-574.0	4.0	3000	7.5	1725	460/3	11	HH406R.1	50'	340
CWC-56	1.106-575.0	4.0	3000	7.5	1770	575/3	9	HH406R.1	50'	340
CWC-63	1.106-576.0	5.0	2000	7.5	1725	230/1	28	HH406R.1	50'	340
CWC-64	1.106-577.0	5.0	2000	7.5	1725	230/3	18	HH406R.1	50'	340
CWC-65	1.106-578.0	5.0	2000	7.5	1725	460/3	9	HH406R.1	50'	340
CWC-66	1.106-579.0	5.0	2000	7.5	1770	575/3	8	HH406R.1	50'	340

BDE SERIES

BELT DRIVE



The **BDE Series** is the electric equivalent of the BD Series. Hotsy belt-drive, triplex pump and cleaning power of 5000 PSI. Both models feature the large cage frame and are equipped with a 50' hose.



- 1765 RPM Motor
- Totally enclosed belt guard
- 12' cord length
- NEMA 4-Electrical Box
- 13" tubed pneumatic tires for easy handling
- Plated steel high-pressure wand w/ side handle
- ETL certified to UL-1776 safety standards

MODEL	PART NO.	GPM	PSI	HP	MOTOR RPM	VOLT/PH	AMPS	PUMP MODEL	PUMP RPM	HOSE	DIMENSIONS	SHIP WT (lbs)
BDE-505009B	1.107-085.0	5.0	5000	20	1765	230/3	48	HH5050R	1650	50'	46"Lx30"Wx36"H	524
BDE-505009C	1.107-086.0	5.0	5000	20	1765	460/3	26	HH5050R	1650	50'	46"Lx30"Wx36"H	524

OPTIONS

PART NO.	DESCRIPTION
8.904-110.0	E-Zee Hose Reel Kit*100' (large cage)

OPTIONS

PART NO.	DESCRIPTION
8.904-113.0	5000 PSI Hose Reel Kit* (large cage)
8.904-115.0	5000 PSI Dual Hose Reel Kit,*† (large cage)

*Kit includes hose reel and mounting hardware

†Includes garden hose reel and high-pressure hose reel

EP SERIES

DIRECT DRIVE



The **EP Series** offers a portable alternative to the electric-powered, cold water pressure washer line featuring the Hotsy direct-drive pump with a 7-year warranty. The EP's functional design is further enhanced by 10" tubed pneumatic tires, a convenient hose-and-gun rack and ETL safety certification.



- 1725 RPM Baldor electric motor
- Steel frame
- Hotsy pump with 7-year warranty
- Insulated wand and fatigue-free gun
- Powder coat finish protection
- ETL safety certification

MODEL	PART NO.	GPM	PSI	HP	VOLT/PH	AMPS	PUMP MODEL	DRIVE	DIMENSIONS	HOSE	SHIP WT (lbs)
EP-201009D	1.106-025.0	2.0	1000	1.5	120/1	15	HE2020S.1	Direct	35"Lx21"Wx24"H	50'	151
EP-301009D	1.106-026.0	3.0	1000	2	120/1	20	HE2825S.1	Direct	35"Lx21"Wx24"H	50'	150
EP-301509A	1.106-027.0	3.0	1500	3	230/1	15	HE2825S.1	Direct	35"Lx21"Wx24"H	50'	157
EP-352009A	1.106-028.0	3.5	2000	5	230/1	20	HHC456R.1	Direct	35"Lx21"Wx24"H	50'	205

OPTIONS EP SERIES

PART NO.	DESCRIPTION
8.904-107.0	EZ Hose Reel Kit 100' (incl. reel & mounting hardware)

HAND-HELD COLD WATER PRESSURE WASHER - ELECTRIC

ET SERIES

Electric-Powered

DIRECT DRIVE



The **ET Series** is the hand-held model of the electric-powered line, delivering cleaning capability up to 1400 PSI. The ET features a reliable direct-drive triplex pump and is ETL safety certified.



- 1725 RPM Motor
- Direct-drive high-pressure pump
- 25' & 50' hose
- Convenient carrying handle
- Remote switch with 10' cord (ET-201409DX2 only)
- Accepts incoming hot water up to 180°F
- Standard auto start/stop (ET-201409DX2 only)

Note: Detergent Injector Sold Separately

MODEL	PART NO.	GPM	PSI	HP	VOLT/PH	PUMP MODEL	DRIVE	DIMENSIONS	HOSE	SHIP WT (lbs)
ET-301109D	1.106-107.0	3.0	1000	2.0	115/1	HHC235R.1	Direct	20"Lx19"Wx17"H	50'	121
ET-201409DX2	1.107-089.0	1.8	1400	2.0	115/1	HE2020S	Direct	20"Lx19"Wx17"H	25'	123

OPTIONS ET SERIES

PART NO.	DESCRIPTION
8.920-952.0	Wall Mount Bracket

OPTIONS ET SERIES

PART NO.	DESCRIPTION
8.929-062.0	Detergent Injector (up to 3 GPM)

*The following pages include
Equipment that can be ordered through our
Specials Department*



Hotsty®

2015

STANDARD SPECIALS EQUIPMENT



Hot Water **ELECTRIC** Pressure Washers

500 SERIES

ELECTRIC HOT WATER



BASE MODEL 558 ON PAGE 2 CAN BE MODIFIED

SPECIAL OPTIONS & CONFIGURATIONS

MODEL(S)	PART NO.	DESCRIPTION
558-559	H-101*	Electronic Ignition
558-559	H-102*	Auto Start / Stop
559	559-SP1	2 HP, 1300 PSI Natural Gas

*Options not sold separately

700 SERIES

ELECTRIC HOT WATER



BASE MODELS 771 & 772 ON PAGE 2 CAN BE MODIFIED

SPECIAL OPTIONS & CONFIGURATIONS

MODEL(S)	PART NO.	DESCRIPTION
771-772	H-106*	Electronic Ignition
771-772	H-107*	Auto Start / Stop

*Options not sold separately

1800 SERIES

ELECTRIC HOT WATER



ALL 1800 SERIES BASE MODELS ON PAGE 5 CAN BE MODIFIED

SPECIAL OPTIONS & CONFIGURATIONS

MODEL(S)	PART NO.	DESCRIPTION
All Models	H-708	2 Stage Gas Valve**

*Up to 750,000 BTU's - for higher rating, contact our Specials Dept. The two stage gas valve includes two thermostat controller and a gas valve with a high and low gas flow ability.

**Contact Specials Dept. for details / Expect extended lead times.

5700/5800 SERIES

ELECTRIC HOT WATER



Shown with modulating gas valve

ALL 5700/5800 SERIES BASE MODELS ON PAGE 5 CAN BE MODIFIED

SPECIAL OPTIONS & CONFIGURATIONS

MODEL(S)	PART NO.	DESCRIPTION
All Models	H-705	2 Stage Gas Valve**

*Up to 750,000 BTU's - for higher rating, contact our Specials Dept. The two stage gas valve includes two thermostat controller and a gas valve with a high and low gas flow ability.

**Contact Specials Dept. for details / Expect extended lead times.

STANDARD SPECIALS EQUIPMENT



Hot Water **ELECTRIC** Pressure Washers

HWE SERIES

ALL ELECTRIC HOT WATER



Shown with special option
stainless steel cabinet



SPECIAL OPTIONS & CONFIGURATIONS

MODEL(S)	PART NO.	DESCRIPTION
HWE-402009F †	HWE-4020-SP	5 HP 575V/3PH (3.5 GPM @ 2000 PSI)
HWE-353009F †	HWE-4030-SP	7.5 HP 575V/3PH
HWE-40 †	HWE-40-SP	460V/3PH Heater only
HWE-50 †	HWE-50-SP	575V/3PH Heater only
All Models	H-600	Float Tank
All Models	H-610	Non-brushed Stainless Steel Heater*

*Exterior cabinet only

MODELS TO BE MODIFIED:

MODEL	PART NO.	GPM	PSI	HP	MOTOR	AMPS	VOLT / PH	KvA HOUR	BTU /	PUMP MODEL	DRIVE	DIMENSIONS	SHIP WT (lbs)
HWE-402009C	1.109-646.0	3.9	2000	6.2	Baldor	55.2	460/3	40.5	138,308	HH306R.1	Belt	34"Lx25"Wx52"H	620
HWE-353009C	1.109-647.0	3.5	3000	7.5	Baldor	59	460/3	40.5	138,308	HH306R.1	Belt	34"Lx25"Wx52"H	640

Hot Water **GAS ENGINE** Pressure Washers

GAS- ENGINE SERIES

BELT-DRIVE

GAS ENGINE HOT WATER



1075BE (Shown with
optional caster wheel kit)

BASE MODELS 965B, 1075BE & 1080BE ON PAGE 6 CAN BE MODIFIED

SPECIAL OPTIONS & CONFIGURATIONS

MODEL(S)	PART NO.	DESCRIPTION
1075BE	H-402*	Steam**
1075BE	H-105	Flow Switch
1075BE †	1075BE-SP	Yanmar 10 HP Diesel Engine (3GPM @ 3000PSI)
1080BE	H-403*	Steam**
1075BE/1080BE	H-406*	Electric Clutch (AX Belts)

*Options not sold separately

12V battery is required, but is not supplied.

**Steam will include a metering valve that when opened will reduce the GPM and PSI allowing the water temp to rise to wet steam.

1200 SERIES

GAS ENGINE HOT WATER



1290SS

ALL 1200 SERIES BASE MODELS ON PAGE 7 CAN BE MODIFIED

SPECIAL OPTIONS & CONFIGURATIONS

MODEL(S)	PART NO.	DESCRIPTION
All Models	H-300*	Steam**
All Models	H-630	Super Duty Kit ***
Honda Models	H640	688 CC's Honda Upgrade
1290SS Only		4.5 GPM @ 5000 PSI, 688 CC's Honda

*Option not sold separately

**Steam will include a metering valve that when opened will reduce the GPM and PSI allowing the water temp to rise to wet steam.

***Super Duty Kit Description: Remove float tank. Replace flow switch with HD pressure switch. Replace unloader with VB80. Remove inlet detergent injector. Replace existing coil wrap with stainless steel coil wrap. Coil wound as a gas coil to reduce soot build up. 12V battery is required, but is not supplied.

STANDARD SPECIALS EQUIPMENT



Hot Water **GAS ENGINE** Pressure Washers

MODEL 5645

GAS ENGINE HOT WATER



SPECIAL OPTIONS & CONFIGURATIONS

MODEL(S)	PART NO.	DESCRIPTION
5645	5645-SP	7 @ 3000 / 700,000 BTU / 20 HP Honda
5645	5645-SP	8 @ 3000 / 700,000 BTU / 24 HP Honda
All Models	H-405*	Steam**

*Option not sold separately

**Steam will include a metering valve that when opened will reduce the GPM and PSI allowing the water temp to rise to wet steam.
12V battery is required, but is not supplied.

Hot Water **DIESEL** Pressure Washers

HCD SERIES

Skid Unit

DIESEL ENGINE HOT WATER



Shown with Stainless Steel cage option H-551, H-553

SPECIAL OPTIONS & CONFIGURATIONS

MODEL(S)	PART NO.	DESCRIPTION
HCD5-5000	HCD5-5000-SP	5.0 @ 5000 27 HP Kohler Diesel, 12V Burner
HCD6-3500	HCD6-3500-SP	5.6 @ 3500 27 HP Kohler Diesel, 12V Burner
HCD-503069E-SP †	HCD5-3000-SP	4.4 @ 3000 16 HP Kohler Diesel, 12V Burner
HCS-503029E-SP †	HCS5-3000-SP	4.8 @ 3000 16 HP Vanguard Gas, 12V Burner*
ALL	H-550	2000 watt Generator / 120V Burner**
ALL	H-551	Stainless Steel Frame
SS Option Only	H-552	Stainless Steel Lifting Cage w/option H-551
SS Option Only	H-553	Stainless Steel Lifting Cage & Drip Pan w/option H-551 only

*HCS comes with plastic fuel tanks and SS top and bottom wrap - Note: Stainless steel options H-551, H-552, H-553 do not apply to this model (call for Stainless steel prices)
12V battery is required, but is not supplied.

HEATING MODULES

9400 SERIES

Heating Modules



Model 9462

ALL 9400 SERIES BASE MODELS ON PAGE 9 CAN BE MODIFIED

SPECIAL OPTIONS & CONFIGURATIONS

MODEL(S)	PART NO.	DESCRIPTION
All Models	H-706	2 Stage Gas Valve**

*Up to 750,000 BTU's - for higher rating, contact our Specials Dept. The two stage gas valve includes two thermostat controller and a gas valve with a high and low gas flow ability.

**Contact Specials Dept. for details / Expect extended lead times.

1200/1800/5700

Heater SERIES

Fuel-burner types available:

- Diesel
- Kerosene
- Home Heating Oil
- Natural Gas



1200 Series Coil-Only Assembly

5700 Series Coil-Only Assembly

SPECIAL OPTIONS & CONFIGURATIONS

MODEL(S)	PART NO.	DESCRIPTION
1200	H-1200	Oil-Fired - 398,000 BTUs
1200	H-1201	NG-Fired - 365,000 BTUs
1800	H-1800	Oil-Fired - 580,000 BTUs
1800	H-1801	NG-Fired - 560,000 BTUs
1800	H-708	2 Stage Gas Valve**
5700	H-5700	Oil-Fired - 920,000 BTUs
5700	H-5701	NG-Fired - 920,000 BTUs
5700	H-705	2 Stage Gas Valve**

1200 Series up to 5.6 GPM @ up to 4,000 PSI

1200 Oil-fired 120V AC / 1PH 5 Amp*

1200 Oil-fired 12V DC*

1200 NG Millivolt

1800 Series up to 6 GPM @ up to 3,200 PSI

1800 Oil-fired 120V AC / 1PH 8 Amp

1800 NG 120V / 1PH 1 Amp (with electronic ignition)

5700 Series up to 9.5 GPM @ up to 3,200 PSI

5700 Oil-fired 120V AC / 1PH 8 Amp

5700 NG 120V / 1PH 1 Amp (with election ignition)

* Please verify voltage on order

**Contact Specials Dept. for details / Expect extended lead times.

TRAILER SPECIALS

Trail Blazer

TRAILER

THE TRAILER ON PAGE 9 CAN BE MODIFIED

SPECIAL OPTIONS & CONFIGURATIONS

MODEL(S)	PART NO.	DESCRIPTION
TRB-3500	H-2501	Low-Level Shutdown*
TRB-3500	H-2502	By-Pass Unloader to 200gal Tank
TRB-3500	H-RED	Painted Red Trailer

*Available with Belt-Drive gas engine units only

Painted red trailer



Shown with 1080BE and optional accessories

TRAILER SPECIALS

HTR TRAILER



- Single or tandem axle models
- Water tank made of high-density, polyethylene (200-gal. on single axle, 330-gal. on the tandem axle trailer)
- Electrical wiring recessed within rugged tubular frame
- Two 3-way ball valves for easy switching of water flow
- 1,000 lb. swivel jack with a 2 5/16-inch ball coupler for quick and easy hook up of the trailer

HTR SPECIAL OPTIONS & CONFIGURATIONS

MODEL(S)	PART NO.	DESCRIPTION
HTR Single Axle 3300 lbs.	HTR3000-SP	Single Axle 3300 lbs.
HTR Tandem Axle 6000 lbs.	HTR6000-SP	Tandem Axle 6000 lbs.
3300/6000		Battery installed on pressure washer
ELECTRIC BRAKE OPTIONS		
6000	N/A	Electric brake one axle
6000	N/A	Electric brake two axle
3300	N/A	Electric brake
3300/6000	HTR-100-SP	Height adjustable hitch. Lunette eye (replaces ball coupler)
3300/6000	HTR-101-SP	2-inch ball coupler (fits height adjustable hitch above)
3300/6000	HTR-102-SP	2-5/16 inch ball coupler (fits height adjustable hitch above)
3300/6000	HTR-103-SP	Kit, breakaway actuator with battery
HYDRAULIC BRAKE OPTIONS		
6000	HTR-200-SP	Hydraulic break one axle, 6000 with 2" ball coupler
6000	HTR-201-SP	Hydraulic break two axle, 6000 with 2" ball coupler
3300	HTR-202-SP	Hydraulic break, 3300 with 2" ball coupler
6000	HTR-203-SP	Hydraulic break one axle, 6000 with height adj. hitch (specify coupler below)
6000	HTR-204-SP	Hydraulic break two axle, 6000 with height adj. hitch (specify coupler below)
3300/6000	HTR-205-SP	Hydraulic break, 3300 with height adj. hitch (specify coupler below)
3300/6000	HTR-206-SP	2-inch ball coupler (fits height adjustable hitch 8.902-451.0 & 8.902-453.0)
3300/6000	HTR-207-SP	2-5/16 inch ball coupler (fits height adjustable hitch 8.902-451.0 & 8.902-453.0)
3300/6000	HTR-208-SP	Coupler, 3-inch Lunette eye (fits height adjustable hitch 8.902-451.0 & 8.902-453.0)
CHEMICAL RACK OPTIONS		
6000	HTR-300-SP	Dual 5 gal. bucket chemical rack
FUEL TANK AND TOOL BOX OPTIONS (Diesel Only)		
6000	HTR-400-SP	ProTech Tool Box with 50 gallon Fuel Tank
HOSES INSTALLED		
3300/6000	HTR-500-SP	High-Pressure Hose 3/8-inch x 100ft, 2-wire, installed
3300/6000	HTR-501-SP	Garden Hose, 3/4-inch x 50ft, installed
HOSE REEL KITS (HOSE NOT INSTALLED)		
3300/6000	HTR-600-SP	Hose reel kit for 100ft of 3/8-inch high-pressure hose
3300/6000	HTR-601-SP	Hose reel kit for 200ft of 3/8-inch high-pressure hose
3300/6000	HTR-602-SP	Hose reel kit for 75ft of 3/4-inch garden hose
MOUNTING KITS		
3300/6000	HTR-700-SP	Machine mounting & plumbing
WHEELS AND FENDERS		
3300/6000	HTR-800-SP	Chrome Wheels, Pair w/ ST205/75d15/C spare tire (2 pair required for 6000)
6000	HTR-801-SP	Chrome Fenders, pair, 6000
3300	HTR-802-SP	Chrome Fenders, pair, 3300
AVAILABLE MACHINES (SEE PRICE LIST FOR MACHINE PRICE)		
HCS, HCD, Belt Drive Gas Engine Series, 1200 Series		

**Does not qualify for free freight program. Call for freight quote.*

Cold Water **GAS ENGINE** Pressure Washers**BD
SERIES****GAS ENGINE COLD WATER****SPECIAL OPTIONS & CONFIGURATIONS**

MODEL(S)	PART NO.	DESCRIPTION
BD-373539	BD-373539-SP	Upgraded 13 HP Honda Electric Start (Sm Cage)
BD-404029	BD-404029-SP	Upgraded 16 HP Vanguard Electric Start (Lg Cage)
BD6-3500	BD6-3500-SP	20 HP Honda Electric Start (Lg Cage)
BD8-3000	BD8-3000-SP	24 HP Honda Electric Start (Lg Cage)
BD10-2000	BD10-2000-SP	24 HP Honda Electric Start (Lg Cage)

* Comes with separate fuel tank

Cold Water **DIESEL ENGINE** Pressure Washers**DIESEL
COLD WATER**

Built on Skid Frame

DIESEL ENGINE COLD WATER**SPECIAL OPTIONS & CONFIGURATIONS**

MODEL(S)	PART NO.	DESCRIPTION
4.3-3000	DCW43000-SP	16 HP Kohler KDW702
5.6-3000	DCW63000-SP	27 HP Kohler KDW1003
8.0-3000	DCW83000-SP	27 HP Kohler KDW1003
5.0-5000	DCW55000-SP	27 HP Kohler KDW1003

Dimensions: 40"Lx37"Wx48"H

All models priced without generator. Contact Specials for additional pricing and lead time for generator option.

Cold Water **BELT DRIVE** Pressure Washers**BELT DRIVE
STATIONARY****ELECTRIC COLD WATER****SPECIAL OPTIONS & CONFIGURATIONS**

MODEL(S)	PART NO.	DESCRIPTION
CWS6-3000	CWS6-3000-SP	15 HP 230V/460V/3PH*
CWS8-3000	CWS8-3000-SP	20 HP 230V/460V/3PH*
CWS10-2000	CWS10-2000-SP	15 HP 230V/460V/3PH*
	H-4000	6-8 GPM Auto Start/Stop w/Shutdown
	H-4001	10 GPM Auto Start/Stop w/Shutdown

Dimensions: 50"Lx28"Wx48"H

* Please verify voltage on order

**BELT DRIVE
PORTABLE****ELECTRIC COLD WATER****SPECIAL OPTIONS & CONFIGURATIONS**

MODEL(S)	PART NO.	DESCRIPTION
CWP5-3000	CWP5-3000-SP230-3	4.8 @ 3000, 10 HP, 230V/3PH
CWP5-3000	CWP5-3000-SP460-3	4.8 @ 3000, 10 HP, 460V/3PH
CWP6-2500	CWP6-2500-SP230-3	5.6 @ 2500, 10 HP, 230V/3PH
CWP6-2500	CWP6-2500-SP460-3	5.6 @ 2500, 10 HP, 460V/3PH
CWP7-2000	CWP7-2000-SP230-3	7.0 @ 2000, 10 HP, 230V/3PH
CWP7-2000	CWP7-2000-SP460-3	7.0 @ 2000, 10 HP, 460V/3PH
CWP8-1800	CWP8-1800-SP230-3	8.0 @ 1800, 10 HP, 230V/3PH
CWP8-1800	CWP8-1800-SP460-3	8.0 @ 1800, 10 HP, 460V/3PH
	H-4002	All CWP Models Time Delay
	H-4003	All CWP Models 575V 3 PH Electrical Upgrade
	H-4004	Auto Start/Stop

Cold Water **ELECTRIC** Pressure Washers

1700 SERIES

ELECTRIC COLD WATER



Shown with optional stainless steel cabinet

ALL 1700 SERIES BASE MODELS ON PAGE 12 CAN BE MODIFIED

OPTIONS		
MODEL(S)	PART NO.	DESCRIPTION
All	H-800	Float Tank
1726	1726-SP	5 HP 575V/3PH / 3.5 GPM @ 2000 PSI
1740	1740-SP †	10 HP 230V/1PH / 4.76 GPM @ 3000 PSI
1742	1742-SP †	10 HP 208V/1PH / 4.76 GPM @ 3000 PSI
1746	1746-SP	10 HP 575V/3PH / 4.76 GPM @ 3000 PSI
1756	1756-SP	10 HP 575V/3PH / 5.93 GPM @ 2500 PSI

BDE SERIES

ELECTRIC COLD WATER



ALL BDE SERIES BASE MODELS ON PAGE 13 CAN BE MODIFIED

OPTIONS		
MODEL(S)	PART NO.	DESCRIPTION
BDE5-3000	BDE5-3000-SP230-1	10 HP 230V/1PH
BDE5-3000	BDE5-3000-SP575-3	10 HP 575V/3PH
BDE5-5000	BDE5-5000-SP208-3	20 HP 208V/3PH
BDE5-5000	BDE5-5000-SP575-3	20 HP 575V/3PH
BDE8-3000	BDE8-3000-SP230-3	20 HP 230V/3PH
BDE8-3000	BDE8-3000-SP460-3	20 HP 460V/3PH
BDE10-2000	BDE10-2000-SP230-3	15 HP 230V/3PH
BDE10-2000	BDE10-2000-SP460-3	15 HP 460V/3PH
BDE8-3000	BDE8-3000-SP575-3	20 HP 575V/3PH
BDE10-2000	BDE10-2000-SP575-3	15 HP 575V/3PH
BDE5-5000	H-1000*	Time Delay Shutdown
BDE5-3, 8-3, 10-2	H-1001*	Time Delay Shutdown
BDE5-3000	H-2000*	Auto Start/Stop
BDE8-3, 5-5, 10-2	H-2001*	Auto Start/Stop

*Options not sold separately

EP SERIES

ELECTRIC COLD WATER



ALL EP SERIES BASE MODELS ON PAGE 13 CAN BE MODIFIED

OPTIONS		
MODEL(S)	PART NO.	DESCRIPTION
All Models	H-3000*	Auto Start
EP 3000	EP 3000-SP	7.5 HP Direct Drive

*Option not sold separately
Please verify voltage at the time of order

CWC SERIES

ELECTRIC COLD WATER



ALL CWC SERIES BASE MODELS ON PAGE 13 CAN BE MODIFIED

OPTIONS		
MODEL(S)	PART NO.	DESCRIPTION
All Models †	H-CWCSS	Stainless Steel

†Indicates ETL certified

Hotsy Hose Reels

Features a sturdy, lockable 360° pivot design. Numerous mounting options. These patented pivot reels are always aligned with the hose for tangle-free pressure washing. Rated at 5000 PSI and 325°F.

Part No.	Description	Length
8.750-486.0	Pivot Reel	100' x 3/8"
8.750-483.0	Pivot Reel	200' x 3/8"
8.750-478.0	Fixed Based	100' x 3/8"
8.750-481.0	Fixed Based	200' x 3/8"



Part No.	Description
8.919-441.0	45° Support Arm for Non-Pivot Reel*
8.919-445.0	90° Support Arm for Non-Pivot Reel*
8.919-448.0	Vertical Support Arm for Non-Pivot Reel*

Additional brackets available on page 45 of the Everything Hotsy catalog.

Fixed Base Hose Reels & Mounting Bracket Options

Features a sturdy, fixed design. Several mounting options. These patented reels are always aligned with the hose for tangle-free pressure washing. Rated at 5000 PSI and 325°F. 2-yr warranty on the swivel.

Hot Water Electric Models	Connector Hose*	List Price	Bracket #1 45° Arm	List Price	Bracket #2 90° Arm	List Price	Bracket #3 Vertical Arm
555SS	8.901-464.0 (4 ft)	\$18.40	8.919-441.0	\$25	8.919-445.0	\$24	8.919-448.0
560SS	8.901-472.0 (6 ft)	\$22.25	8.919-441.0	\$25	8.919-445.0	\$24	8.919-448.0
680SS	8.901-464.0 (4 ft)	\$18.40	8.919-441.0	\$25	8.919-445.0	\$24	8.919-448.0
790SS	8.901-464.0 (4 ft)	\$18.40	8.919-441.0	\$25	8.919-445.0	\$24	8.919-448.0
795SS	8.901-464.0 (4 ft)	\$18.40	8.919-441.0	\$25	8.919-445.0	\$24	8.919-448.0
795SS-208	8.901-464.0 (4 ft)	\$18.40	8.919-441.0	\$25	8.919-445.0	\$24	8.919-448.0
895SS	8.901-464.0 (4 ft)	\$18.40	8.919-441.0	\$25	8.919-445.0	\$24	8.919-448.0
800 Series	8.901-472.0 (6 ft)	\$22.25	8.919-441.0	\$25	8.919-445.0	\$24	8.919-448.0

Hotsy 360° Pivot Hose Reels & Mounting Bracket Options

Features a sturdy, lockable 360° design. Several mounting options. These patented reels are always aligned with the hose for tangle-free pressure washing. Rated at 5000 PSI and 325°F. 2-yr warranty on the swivel.

NOTE: Models come standard with pivot reel receptacle - no additional bracket is required.

NOTE: Pressure washer hose not included

*Required to connect hose reel to pressure washer. Can be found on page 42 of Everything Hotsy catalog.

Hot Water Electric Models	Connector Hose*
555SS	8.901-460.0 (3 ft)
560SS	8.901-464.0 (4 ft)
680SS	8.901-464.0 (4 ft)
790SS	8.901-464.0 (4 ft)
795SS	8.901-464.0 (4 ft)
795SS-208	8.901-464.0 (4 ft)
895SS	8.901-464.0 (4 ft)
800 Series	8.901-472.0 (6 ft)

Hotsy Trigger Guns



- **PSI:** 5000
- **GPM:** 10.5
- **Temperature:** 320°F
- 3/8" FPT inlet x 1/4" FPT outlet



Part No.	Description
8.751-235.0	Hotsy Gun



Tuff-Skin 1-Wire 4000 PSI Hose

Part No.	Size	ID	Temp	Fittings	PSI
3/8" MPT Swivel x 3/8 MPT Swivel					
8.739-016.0	50'	3/8	275°F	SWxSW	4000

A+ Rotary Surface Cleaners

- 4000 PSI
- Max. temperature 212°F
- 8 GPM
- Stainless Steel housing
- 21" or 24" diameter surface cleaning
- 4 caster wheels
- Low wall clearance - cleans right up to the wall



Part No.	Description
8.753-572.0	A+SC21 Rotary Surface Cleaners
8.753-573.0	A+SC24 Rotary Surface Cleaners

Hotsy's **DIRTY DOZEN DETERGENTS**

For soap recommendations, start with these 12 Category Leaders



#1 **BREAKTHROUGH!**

Hotsy's best all-purpose detergent

Highly concentrated with dilution ratio of 150 to 1. Whether removing grease or cleaning a finely painted automobile, Breakthrough! is the best all around "go to" detergent. Breakthrough's high foaming action attacks dead oxidized paint and can be used in hard and cold water applications.

#2 **TRANSPORT VEHICLE WASH**

Hotsy's most economical detergent for vehicles

If it has wheels, Transport is the detergent of choice. Autos, buses, motor homes, mobile homes, tractor trailers are just a few applications for this economical liquid detergent. Great when used as a pre-spray for engine compartment cleaning and safe on all painted surfaces, stainless steel, aluminum and glass.

#3 **RIPPER 1**

Hotsy's best heavy-duty degreaser

Ripper 1 is specially formulated for degreasing heavy equipment and hard to remove road film on tractor trailers, end loaders, excavators and back hoes, yet still safe on painted surfaces. Non-caustic and user-friendly.

#4 **HOTSY BROWN**

Hotsy's best detergent for oil field cleaning

A degreasing detergent specially formulated for the oil field that also works great on oil soaked or stained surfaces such as, frames and equipment. A non-Butyl based product that works good in cold water, Hotsy Brown is a caustic based product and should not be used on fine painted surfaces or magnesium, galvanized or aluminum.

#5 **ALUMINUM BRIGHTENER**

Hotsy's best selling aluminum brightener

This highly concentrated acid with dilution ratios up to 20 to 1, attacks oxidized aluminum leaving a "like new" look to the surface after the initial application. Not to be used on new aluminum or aluminum that is not oxidized.

#6 **VERDE ALL PURPOSE**

Our environmentally-friendly green general purpose cleaner

A unique blend of environmentally preferred chemicals that provide great cleaning capabilities in all water conditions and all water temperatures. Superior foaming and fast-rinsing provide great results while saving money and the environment.

#7 **SALT LICK**

Hotsy's answer to removing salt and de-icing solutions

Salt Lick is formulated to remove salt, calcium chloride and de-icing solution used on winter roads by breaking down the crystalline structure of ice melt products and prevents them from re-crystallizing so they can be washed away. Salt Lick is a dual-purpose concentrated detergent attacking heavy soils and road film.

#8 **CARBOCHLOR**

Hotsy's #1 choice for cleaning food preparation areas

A special emulsifying formula with high powered bleach for food processing plants. Excellent on tough odors, stains, dirt, oils and fats left behind on equipment, floors, and walls. NSF recognized for use in Federally Inspected food plants.

#9 **CON-B-GONE**

Removing green concrete from trucks & tools

A fast acting acidic product that when applied to ready mix trucks, forms and tools softens dried concrete splatter allowing it to be rinsed away with a hot or cold water pressure washer. Con-B-Gone's foaming formula makes application over large areas quick and easy. A Hotsy Foamer increases dwell time and maximizes end results!

#10 **TUBMATE GEN. PURPOSE**

Hotsy's heavy-duty automatic parts washer detergent

A phosphate-free, biodegradable, super-concentrated liquid. Works great with automatic detergent injectors; can be automatically metered into aqueous parts washers. Quick oil release and solvent free. Heavy duty rust and corrosion inhibitor package protects against flash rusting; defoamers reduce foam in your aqueous parts washer.

#11 **FAT CAP BRICK**

Hotsy's easy-to-use liquid graffiti remover

The #1 alternative to sand blasting or painting over unsightly graffiti. Designed for use on exterior brick, masonry and concrete surfaces. Hotsy Fat Cap Graffiti Remover - Brick, Masonry and Concrete cleaner is deep penetrating and fast acting for effective and thorough loosening of spray paint graffiti and easy removal of the graffiti from the surface being treated.

#12 **CITRUS CLEAN**

"Beefs" up the cleaning action of any Hotsy soap

This citrus-based detergent additive increases any detergent's cleaning and degreasing power and is a great degreaser in its own right, plus it also enhances rinsing. Contains d-limonene which is a great "natural" degreaser.